Technical data sheet

Advanced Engineering Ltd

Guardian House, Stroudley Road Basingstoke, Hampshire, RG24 8NL. UK Tel +44(0)1256 460300 www.advancedengineering.co.uk



All-White®

Ceiling tile restorer



All-White® ceiling tile restorer is a quick and easy way of re-colouring stained ceiling tiles to their original whiteness - Saving you the time and expense of sourcing a new tile

PRODUCT SPECIFICATION

Name	All-White®
Product Code	S010157GB
Packing Quantity (ml, L)	12 x 400ml
Packing Size (L x H x D cm)	21 x 25 x 27
Shipping Weight (kg)	5.53
Shipping Volume (m³)	0.0142
Soils	N/A

Special Features

- Stain Blocking formulation
- Upward spraying nozzle

Directions of use







Shake the can vigorously for 2 minutes (with the ball rattling) prior to use. Spray All-White® in an upwards direction to restore the ceiling tile. Ensure that the spray only comes into contact with the surfaces you want to restore. All-White® should be dry within 30 minutes of use.

NOTE: To ensure that the nozzle remains clear after using All-White®, point the can downwards over a disposable surface. Then, spray until only propellant is expelled.

Caution: Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray onto a naked flame or any incandescent material. Contains isodecyloxpropylamine acetate. May produce an allergic reaction.





All-White® UN1950 Danger Contains Acetone

EUH066: Repeated exposure may cause skin dryness or cracking. EUH208: Contains isodecyloxpropyl amine acetate. May produce an allergic reaction. H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated H315: Causes skin irritation. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. H412: Harmful to aquatic life with long lasting effects. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P280: Wear protective gloves / protective clothing / eye protection / face protection. P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P410+412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C.



INVESTOR IN PEOPL

This product should only be used by trained operatives. The "directions for use" are recommendations only; correct use will depend upon circumstances. To the extent permitted, no liability can be accepted for loss resulting from its use. Advanced Engineering follows a policy of continual product improvement. For this reason, some materials and specifications could change without notice. Consult Safety Data Sheet for full safety information. Always wear suitable PPE.