## PORTABLE DEVICES

## LOCAL AIR CONDITIONERS

- Cooling Capacity 3,5 kW
- · Ideal Room Size 12–24 m<sup>2</sup>
- · Energy Class A
- · Clock, Timer ON-OFF Function
- · Sound Pressure Level max. 54 dB(A)
- Condensate Evaporation Function
- · Wheels for Better Mobility
- Easy Maintenance

MODEL	APM-12PTH			
Rated Cooling Capacity	P <sub>rated</sub> in Cooling	3,5	kW	
Rated Heating Capacity	P <sub>rated</sub> in Heating	3	kW	
Rated Power Input (Cooling)	P <sub>EER</sub>	1,35	kW	
Rated Power Input (Heating)	P <sub>COP</sub>	1,1	kW	
EER	EER	2,6	-	
COP	COP	2,8	-	
Sound Power Level	L <sub>WA</sub>	64	db(A)	
Slobal Warming Potential	GWP	3	kg eq. CO <sub>2</sub>	
Energy Class	Cooling / Heating	A / -	-	
Refrigerant	Type / Charge	R290 / 0,3	type / kg	
Dptimal Room Size	Area	12-24	m <sup>2</sup>	
/oltage	-	~ 220–240	V	
Frequency		50	Hz	
Rated Current		6 / 5,2	A	
Air Flow		320 / 350 / 380	m³ / hour	
Sound Pressure Level	Lp	52 / 53 / 54	db(A)	
lose for Warm Air Discharge	Length / Diameter	150 / 16	cm	
Dehumidification		31	liters / day	
Product Dimensions	(W × H × D)	444 × 723 × 361	mm	
Packaging Dimensions	(W × H × D)	495 × 880 × 420	mm	
let Weight	-	35	kg	
iross Weight	-	39	kg	

\* The unit is filled with a flammable refrigerant R290 (CH<sub>3</sub>CH<sub>2</sub>CH<sub>3</sub>).

\* Hermetically sealed system.



## SINCLAIR CORPORATION LTD. SINCLAIR-WORLD.COM | SINCLAIR-SOLUTIONS.COM E-MAIL: INFO@SINCLAIR-SOLUTIONS.COM

This catalogue is informative only and does not constitute a binding offer from the side of Sinclair Corporation Ltd. The pictures of units and accessories are illustrative only.

sinclair

The company takes no responsibility for any damage arising out of using or interpretation of this catalogue. The contents of this catalogue is protected by copyright of Sinclair Corporation Ltd.